



ALUMINIO RUEDAS

E11

VERSION: 161018
Page: 1/2

NITROSYNTHETIC ENAMEL

DEFINITION

ALUMINIO RUEDAS is a metallic aluminium cellulose enamel. Satin finish for painting industrial applications. Fast drying and high covering power.

ALUMINIO RUEDAS does not comply with Directive 2004/42/EC, Annex II B, so it shall only be applied to coatings not included in such directive or in installations which comply with Directive 1999/13/EC.

PHYSICAL CHARACTERISTICS

| | | |
|----------------------------|-------------------------|---------|
| Nature: | Nitrosynthetic | |
| Colour: | Metal | |
| Appearance: | Glossy | |
| Specific weight: | 0,9 kg/l at 20°C | |
| Dry film thickness: | 40 microns | 2 coats |
| Yield: | 12-15 m ² /l | |
| Voc: | 788 g/l | |
| Solid content: | 12 % | |

SURFACE PREPARATION

| PROCESS | | Paint OEM | Primer |
|---------|------|-----------|--------|
| | P360 | ✓ | ✓ |
| | DA93 | ✓ | ✓ |

APPLICATION

MIXING RATIO

APPLICATION METHOD

| ALUMINIO RUEDAS | A + C | | S | APPLICATION METHOD | | | | | |
|-----------------|----------------|--|---------------------|--------------------|---------|-------|---------|----|----|
| | 100:150 volume | | 20'' F/4 at 20°C | mm | bar | cm | 2 | 5' | |
| SO72 | 100:150 volume | | 20'' F/4 at 20°C | | 1,3-1,5 | 3-3,5 | 15 - 20 | 2 | 5' |
| | | | | | 1,3-1,5 | 3-3,5 | 15 - 20 | | |
| | | | | | 1,3-1,5 | 3-3,5 | 10 | | |

EQUIPMENT CLEANING

Clean with a cleaning thinner.

SAFETY

Follow instructions of product label. For more information check the Safety Data Sheet. Compliant with the National Statutory Regulation for Health and Safety at Work and Waste Disposal.

STORAGE

Store the product in a ventilated place far from direct exposure to sunlight. Keep between +5°C and +30°C.

SHELF LIFE

One year in unopened original packaging.

SUGGESTION:

You will obtain an approximately dark colour depending on the application distance and the paint component of the product.

For any technical information contact with our Customer Attention Service or our Technical Department.
ROBERLO SA declines any responsibility due to an incorrect use of the product.